



SAFETY DATA SHEET

US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date 18-Feb-2022 Revision Date 18-Feb-2022 Revision Number 1

1. Identification

Product identifier

Product Name Power Foam®

Other means of identification

Product Code(s) APFSC

UN/ID no UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Cleaner

Restrictions on use No specific uses advised against are identified

Details of the supplier of the safety data sheet

Initial supplier identifier	Manufacturer Address
AMSOIL INC. Bay Adelaide Centre, East Tower 22 Adelaide St. W Toronto, ON, Canada M5H 4E3 T:+1 877-822-5172	AMSOIL INC. One AMSOIL Center Superior, WI 54880, USA T: +1 715-392-7101

E-mail compliance@amsoil.com

Emergency telephone number

Emergency telephone CHEMTREC: Within USA and Canada: 1-800-424-9300
Outside the USA and Canada: +1 703-741-5970
(collect calls accepted) 24/7

2. Hazard(s) identification

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1B
Flammable aerosols	Category 1

Label elements

Danger

Hazard statements

Extremely flammable aerosol.
Causes skin irritation.
Causes serious eye damage.
May cause cancer.
Harmful to aquatic life.



Precautionary Statements - Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection and face protection. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label).
Eyes
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Skin
IF ON SKIN: Wash with plenty of water and soap. If skin irritation occurs: Get medical advice and attention. Take off contaminated clothing and wash it before reuse.

Precautionary Statements - Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

Other information

Very toxic to aquatic life with long lasting effects. Very toxic to aquatic life.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Hydrogenated base oil	64742-94-5	10 - <25	-	-
Hydrogenated base oil	64742-52-5	10 -< 20	-	-
Ethanol, 2-butoxy-	111-76-2	10 -< 20	-	-
Propane	74-98-6	5 -< 10	-	-
Naphthalene, 2-methyl-	91-57-6	5 - <10	-	-
Naphthalene, 1-methyl-	90-12-0	1 - < 5	-	-
Naphthalene	91-20-3	1 - <5	-	-
Morpholine	110-91-8	1 - < 3	-	-

*The exact percentage (concentration) of composition has been withheld as a trade secret.



Chemical Additions

The classification as a carcinogen does not apply as it can be shown that the substance(s) contain(s) less than 3% DMSO extract as measured by IP 346.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical advice/attention.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation. Redness. May cause blindness. May cause redness and tearing of the eyes. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness and difficulty breathing.
----------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Symptoms may be delayed. Treat symptomatically.
--------------------	---

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Use extinguishing agent suitable for type of surrounding fire. Use water spray to cool fire-exposed containers.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Risk of ignition. Vapors may travel to source of ignition and flash back. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Containers can burst or explode when heated, due to excessive pressure build-up. Damaged cylinders should be handled only by specialists. Containers may explode when heated.
Hazardous combustion products	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.



6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor. Prevent materials or runoff from entering drains, sewers, streams, ground water or bodies of water.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Prevent product from entering drains.
Reference to other sections	For additional information see: Section 8: Exposure controls/personal protection; Section 12: Ecological information; Section 13: Disposal considerations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Avoid contact with used product. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.
-------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Do not reuse empty containers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Keep at a temperature not exceeding 50 °C.
--------------------	--

8. Exposure controls/personal protection

Control parameters

Exposure Limits	Under conditions which may generate mists, the following exposure limits are recommended: Long-term exposure limit (8-hour TWA): 5 mg/m³. Short-term exposure limit (15-minute): 10 mg/m³.
-----------------	--



Chemical name	ACGIH TLV	OSHA PEL	NIOSH	
Ethanol, 2-butoxy- 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³	
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³	
Naphthalene, 2-methyl- 91-57-6	TWA: 0.5 ppm S*	-	-	
Naphthalene, 1-methyl- 90-12-0	TWA: 0.5 ppm S*	-	-	
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m³ STEL: 15 ppm STEL: 75 mg/m³	
Morpholine 110-91-8	TWA: 20 ppm S*	TWA: 20 ppm TWA: 70 mg/m³ (vacated) TWA: 20 ppm (vacated) TWA: 70 mg/m³ (vacated) STEL: 30 ppm (vacated) STEL: 105 mg/m³ (vacated) S* S*	IDLH: 1400 ppm TWA: 20 ppm TWA: 70 mg/m³ STEL: 30 ppm STEL: 105 mg/m³	
Chemical name	Alberta	British Columbia	Ontario	Quebec
Ethanol, 2-butoxy- 111-76-2	TWA: 20 ppm TWA: 97 mg/m³	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
Propane 74-98-6	TWA: 1000 ppm	-	TWA:	TWA: 1000 ppm TWA: 1800 mg/m³
Naphthalene, 2-methyl- 91-57-6	-	TWA: 0.5 ppm Skin	TWA: 0.5 ppm Skin	TWA: 0.5 ppm Skin
Naphthalene, 1-methyl- 90-12-0	-	TWA: 0.5 ppm Skin	TWA: 0.5 ppm Skin	TWA: 0.5 ppm Skin
Naphthalene 91-20-3	TWA: 10 ppm TWA: 52 mg/m³ STEL: 15 ppm STEL: 79 mg/m³ Skin	TWA: 10 ppm Skin	TWA: 10 ppm Skin	TWA: 10 ppm Skin
Morpholine 110-91-8	TWA: 20 ppm TWA: 71 mg/m³ Skin	TWA: 20 ppm Skin	TWA: 20 ppm Skin	TWA: 20 ppm TWA: 71 mg/m³ Skin

Biological occupational exposure limits

Chemical name	ACGIH
Ethanol, 2-butoxy- 111-76-2	200 mg/g creatinine - urine (Butoxyacetic acid with hydrolysis) - end of shift
Naphthalene 91-20-3	- (1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.



Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles). Face protection shield.
Hand protection	Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	Clear to milky white
Odor	Mild hydrocarbon
Odor threshold	No information available

Property	Values	Remarks • Method
pH		No data available
Melting point / freezing point		No data available
Initial boiling point and boiling range		No data available
Flash point	104 °C / 219.2 °F	Estimated
Evaporation rate		No data available
Flammability		No data available
Flammability Limit in Air		
Upper flammability or explosive limits	9.5 % (V)	Estimated
Lower flammability or explosive limits	2.2 % (V)	Estimated
Vapor pressure	2,895 - 3,585 hPa (20 °C) 6,205 - 7,032 hPa (54 °C)	No data available
Vapor density		No data available
Relative density		No data available
Water solubility		No data available
Solubility(ies)		No data available
Partition coefficient		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

Other information	
Explosive properties	No information available.
Oxidizing properties	No information available.
Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Liquid Density	No information available
Bulk density	No information available



10. Stability and reactivity

Reactivity	None under normal use conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition can lead to release of irritating and toxic gases and vapors: Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Redness. Burning. May cause blindness. May cause redness and tearing of the eyes. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness and difficulty breathing.
----------	--

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (oral)	989.90 mg/kg
ATEmix (dermal)	946.70 mg/kg
ATEmix (inhalation-dust/mist)	3.13 mg/l
ATEmix (inhalation-vapor)	376.30 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrogenated base oil	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 590 mg/m³ (Rat) 4 h
Hydrogenated base oil	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Ethanol, 2-butoxy-	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h



Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propane	-	-	> 800000 ppm (Rat) 15 min
Naphthalene, 2-methyl-	= 1630 mg/kg (Rat)	-	-
Naphthalene, 1-methyl-	= 1840 mg/kg (Rat)	-	-
Naphthalene	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 0.4 mg/L (Rat) 4 h
Morpholine	= 1050 mg/kg (Rat)	310 - 810 mg/kg (Rabbit)	> 8000 ppm (Rat) 8 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation. Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Causes serious eye damage.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Hydrogenated base oil 64742-52-5	A2	Group 1	Known	X
Ethanol, 2-butoxy- 111-76-2	A3	Group 3	-	-
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
Morpholine 110-91-8	-	Group 3	-	-

Legend

- ACGIH (American Conference of Governmental Industrial Hygienists)**
 - A2 - Suspected Human Carcinogen
 - A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)**
 - Group 1 - Carcinogenic to Humans
 - Group 2B - Possibly Carcinogenic to Humans
 - Group 3 - Not Classifiable as to Carcinogenicity in Humans
- NTP (National Toxicology Program)**
 - Known - Known Carcinogen
 - Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)**
 - X - Present

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	Due to the viscosity, this product does not present an aspiration hazard.

12. Ecological information

Ecotoxicity	Very toxic to aquatic life with long lasting effects. Harmful to aquatic life.
--------------------	--



Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hydrogenated base oil 64742-94-5	-	LC50: =19mg/L (96h, Pimephales promelas) LC50: =2.34mg/L (96h, Oncorhynchus mykiss) LC50: =1740mg/L (96h, Lepomis macrochirus) LC50: =45mg/L (96h, Pimephales promelas) LC50: =41mg/L (96h, Pimephales promelas)	-	EC50: =0.95mg/L (48h, Daphnia magna)
Hydrogenated base oil 64742-52-5	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
Ethanol, 2-butoxy- 111-76-2	-	LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	-	EC50: >1000mg/L (48h, Daphnia magna)
Naphthalene 91-20-3	-	LC50: 0.91 - 2.82mg/L (96h, Oncorhynchus mykiss)	-	EC50: 1.09 - 3.4mg/L (48h, Daphnia magna)
Morpholine 110-91-8	EC50: =28mg/L (96h, Pseudokirchneriella subcapitata)	LC50: =350mg/L (96h, Lepomis macrochirus) LC50: 375 - 460mg/L (96h, Oncorhynchus mykiss) LC50: >1000mg/L (96h, Brachydanio rerio)	-	-

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Hydrogenated base oil 64742-94-5	6.1
Ethanol, 2-butoxy- 111-76-2	0.81
Propane 74-98-6	2.3
Naphthalene, 2-methyl- 91-57-6	3.86
Naphthalene 91-20-3	3.6
Morpholine 110-91-8	-2.55

Mobility in soil No information available.

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment, Dispose of in accordance with local regulations, Dispose of waste in accordance with environmental legislation.



Contaminated packaging	Do not reuse empty containers.
California waste information	This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT	
UN/ID no	UN1950
Proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Reportable Quantity (RQ)	(Naphthalene: RQ (kg)= 45.40) Naphthalene: RQ (lb)= 100.00
Reportable quantity kg (calculated)	Naphthalene: RQ (kg)= 908.00
Reportable quantity lbs. (calculated)	Naphthalene: RQ (lb)= 2000.00
Special Provisions	N82
DOT Marine Pollutant	I
Marine pollutant	Hydrogenated base oil, Naphthalene
Description	UN1950, AEROSOLS, 2.1, Marine pollutant (Hydrogenated base oil, Naphthalene)
Emergency Response Guide Number	126
TDG	
UN/ID no	UN1950
Proper shipping name	AEROSOLS
Hazard class	2.1
Special Provisions	80, 107
Marine pollutant	Hydrogenated base oil, Naphthalene.
Description	UN1950, Aerosols, 2.1
IATA	
UN number or ID number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
ERG Code	10L
Special Provisions	A145, A167, A802
Description	UN1950, Aerosols, flammable, 2.1
IMDG	
UN number or ID number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
EmS-No	F-D, S-U
Special Provisions	63,190, 277, 327, 344, 381, 959
Marine pollutant	P
Marine pollutant	Hydrogenated base oil
Description	UN1950, AEROSOLS (Hydrogenated base oil), 2.1, Marine pollutant

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable



International Inventories

Contact supplier for inventory compliance status

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Ethanol, 2-butoxy- - 111-76-2	1.0
Naphthalene - 91-20-3	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Naphthalene 91-20-3	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Naphthalene - 91-20-3	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethanol, 2-butoxy- 111-76-2	X	X	X
Naphthalene, 2-methyl- 91-57-6	X	-	-
Propane 74-98-6	X	X	X
Naphthalene, 1-methyl- 90-12-0	X	X	X
Naphthalene 91-20-3	X	X	X
Morpholine 110-91-8	X	X	X



U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION			
TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Key literature references and sources for data used to compile the SDS

U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Issuing Date	18-Feb-2022
Revision Date	18-Feb-2022
Revision Note	Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

