

Save up to 25%

Buy Online



PROTECTION | PERFORMANCE
you demand. | you deserve.™

100% Synthetic DCT Fluid

Dual-clutch transmissions (DCTs) are automatic transmissions based on the architecture of manual transmissions. The complex system essentially consists of two manual transmissions in the same housing. As one clutch is engaged, the other readies the next appropriate gear, minimizing the interruption of power and improving performance and efficiency. A specially formulated fluid is required to maintain the high-performance output of these advanced transmissions. AMSOIL 100% Synthetic DCT Fluid is designed to protect high-tech dual-clutch transmissions during the most intense, high-heat operating conditions. It provides the fast, smooth shifts drivers expect.

Excellent Friction Durability

Dual-clutch transmissions are capable of seamless, split-second shifts but can suffer from shudder or lurching at slow speeds. AMSOIL 100% Synthetic DCT Fluid is engineered to prevent shudder in sophisticated dual-clutch transmissions. Its frictional properties provide superior protection and consistently produce fast, smooth shifts. AMSOIL Synthetic DCT Fluid's exceptional durability ensures stability in stop-and-go traffic. It promotes stable synchronizer engagements, extending the life of the transmission.

Outstanding Wear Protection

AMSOIL Synthetic DCT Fluid resists the extreme heat in today's high-temperature DCTs to provide complete protection for gears, bearings and other vital parts. Its high film strength and anti-wear/extreme-pressure additives are specifically designed to protect the metal surfaces of DCTs.

Resists Heat and Oxidation

Maintaining proper viscosity at extreme temperatures is crucial to protect the components of a dual-clutch transmission. AMSOIL Synthetic DCT Fluid provides complete protection during the intense conditions native to high-performance sports sedans and supercars.

Superior Shear Stability

Transmission fluid can shear at the molecular level as it passes between gear teeth. This leads to reduced viscosity and decreased wear protection. AMSOIL Synthetic DCT Fluid resists shear and provides consistent viscosity, even in the extreme stress of high-horsepower, high-torque applications.

DATA SHEET



- **Outstanding** wear protection.
- **Excellent** performance in extreme heat and cold.
- **Designed** to prevent shudder.

Buy Online

TYPICAL TECHNICAL PROPERTIES
100% SYNTHETIC DCT FLUID (DCT)

Table with 2 columns: Property and Value. Rows include Kinematic Viscosity @ 100°C, cSt (ASTM D445) 7.7, Kinematic Viscosity @ 40°C, cSt (ASTM D445) 38.8, Viscosity Index (ASTM D2270) 171, Pour Point °C (°F) (ASTM D97) -58 (-72), Flash Point °C (°F) (ASTM D92) 230 (446), Fire Point °C (°F) (ASTM D92) 244 (471), Four-Ball Wear Test (ASTM D4172B @ 40 kg, 75°C, 1200 rpm, 1 hr), Scar, mm 0.41, Brookfield Viscosity @ -40°C, cP (ASTM D2983) 8822.

APPLICATIONS

Use in dual-clutch transmissions that require any of the following specifications:

BMW 83 22 2 148 578, 83 22 2 148 579, 83 22 0 440 214, 83 22 2 433 157, 83 22 2 147 477, DCTF-1, MTF-LT-5 • Chrysler 68044345 • Citroen/Peugeot 9734.S2 • Ferrari/Shell TF DCTF-3 • Fiat BOT 341 • Ford WSS-M2C-936-A, WSS-M2C200-D2, XT-11-QDC, XT-14-L • Mercedes-Benz 236.21, 236.25 • Mitsubishi Dia-Queen SSTF-I • Nissan GT-R Transmission Oil R35 Special • Pentosin FFL-2, FFL-3, FFL-4 • Porsche 999.917.080.00, 043 207 29, 043 207 30, 000 430 20 • Renault BOT 450 • Volvo 1161838, 1161839 • G 052 182, G 052 529 (A2, A1 & A6), TL 521 82 • McLaren applications requiring FFL-4 fluid

SERVICE LIFE

AMSOIL 100% Synthetic DCT Fluid should be changed according to your vehicle manufacturer’s recommendations.

WARRANTY

AMSOIL products are backed by a Limited Liability Warranty. For complete information visit AMSOIL.com/warranty.aspx.

HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended applications and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available via the Internet at AMSOIL.com or upon request at 715-392-7101. Keep Out of Reach of Children. Recycle used oil and bottle.

*All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use.



AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.

