



DATA SHEET

OE Synthetic Automatic Transmission Fluid

Modern automatic transmissions are more complicated than their predecessors. Today's designs feature more gears, clutch packs and narrow oil passageways that require a steady supply of high-quality fluid. Without it, wear and sludge formation can lead to reduced performance and even failure, requiring thousands of dollars in repairs. AMSOIL OE Synthetic Automatic Transmission Fluid provides passenger-car/light-truck transmissions excellent wear protection, sludge resistance and extreme-temperature performance throughout original equipment manufacturer (OEM)-recommended drain intervals.

Outstanding Wear Protection

AMSOIL OE Synthetic ATF is durable. In normal and severe service, it resists wear to the transmission's valve body, gears, clutch plates and other vital parts, helping today's complex and demanding transmissions achieve long life.

Resists Varnish

In elevated heat, AMSOIL OE Synthetic ATF's thermally stable formulation guards against the harmful effects of thermal breakdown. It resists the formation of varnish that can stick valves, threatening transmission performance and life. OE Synthetic ATF also resists heat-related evaporation and viscosity loss to help components stay clean and remain protected.

Reliable Cold-Weather Performance

AMSOIL OE Synthetic ATF remains fluid in sub-zero temperatures. It resists thickening and flows quickly for fast, reliable shifts during cold starts. Its excellent low-temperature fluidity also maximizes fuel efficiency.

Excellent Leak Protection

Formulated with seal conditioners, AMSOIL OE Synthetic ATF helps prevent seals and gaskets from drying out and cracking, reducing the risk of fluid leaks.

Promotes Smooth, Shudder-Free Shifts

AMSOIL OE Synthetic ATF is formulated with friction modifiers that promote fast, smooth clutch engagement. As a result, drivers experience fast shift response and torque transfer for maximum drivability.



- **Protects** against wear.
- **Resists** harmful sludge.
- **Excellent** cold-weather performance.
- **Guards** against leaks.
- **Promotes** smooth, shudder-free shifts.



TYPICAL TECHNICAL PROPERTIES
AMSOIL OE Multi-Vehicle Synthetic Automatic Transmission Fluid (OTF)
AMSOIL OE Fuel-Efficient Synthetic Automatic Transmission Fluid (OTL)

Table with 3 columns: Property, OTF, OTL. Rows include Kinematic Viscosity @ 100°C, Kinematic Viscosity @ 40°C, Viscosity Index, Pour Point, Flash Point, and Brookfield Viscosity.

APPLICATIONS

Use AMSOIL OE Multi-Vehicle Synthetic Automatic Transmission Fluid in transmissions and other applications that require any of the following specifications:

Allison C-4, TES-389; BMW 7045E, 8072B, LA 2634, LT 71141; Chrysler Mopar* ASRC, 68089195AA, 68049954AA; Ford MERCON*, MERCON* V, ESP-M2C166-H, FNR5, M2C924-A, XL-12; GM DEXRON* III, DEXRON* II; Honda/Acura ATF-Z1; Hyundai/Kia SP-II, SP-III, Red-1; IDEMITSU K17; JASO 1A; JWS 3309, 3314, 3317; MAN 339 Type V-1, 339 Type V-2, 339 Type Z-1, 339 Type Z-2, 339F; Mazda ATF-M III, ATFMV, F-1; Mercedes Benz 236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11, 236.91; Mitsubishi SP-II, SP-III, ATF-J2; Nissan Matic-D, Matic-J, Matic-K, 402; SAAB 3309; Shell 3403, LA 2634; Subaru ATF, ATF-HP; Suzuki 3314, 3317; Texaco ETL-7045E, ETL-8072B, N402; Toyota Type T, T-II, T-III, T-IV; Voith 55.6335; Volvo 97340, 97341; VW/Audi G 052 162, G 052 990, G 055 025; ZF TE-ML 03D, 04D, 05L, 09, 11A, 11B, 14A, 14B, 16L, 17C, 20B, 21L.

Note: Not for use with CVT or Ford Type F applications.

AMSOIL warrants the use of this product for Chrysler ATF+4® applications above -38°F. Product does not meet the cold temperature requirement of ATF+4 at -40°F. For warranty information, visit AMSOIL.com/warranty.aspx.

Use AMSOIL OE Fuel-Efficient Synthetic Automatic Transmission Fluid in transmissions and other applications that require any of the following specifications:

Aisin-Warner AW-1; BMW 83 22 0 142 516, 83 22 2 152 426; Chrysler MOPAR* 68157995AA, SP-IV, 68218925AB; DSIH 6p805; Ford MERCON* LV SP; GM DEXRON* VI; Honda/Acura DW-1*, Type 3.0; Hyundai/Kia SP-IV, SPH-IV, SP-IV-RR, NWS-9638, SP4-M; JASO 1A-LV; JWS 3324; Mazda ATF FZ; Mercedes Benz 236.12, 236.14, 236.15, 236.41; Mitsubishi SP-IV, ATF J3, ATF-PA, ATF-MA1; Nissan Matic-S, Matic-W; SAAB 93 165 147;

Shell M-1375.4, M-1375.5, M-1375.6, M-L12108; Toyota WS; Volvo 31256774; VW/Audi G 055 005, G 055 162, G 060 162; ZF S671 090 255.

Note: Not for use with CVT applications.

SERVICE LIFE

AMSOIL OE Synthetic Automatic Transmission Fluid should be changed according to your vehicle manufacturer's recommendations.

AMSOIL PRODUCT WARRANTY

AMSOIL products are backed by a Limited Liability Warranty. For complete information visit AMSOIL.com/warranty.aspx.

HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available via the Internet at AMSOIL.com or upon request at 715-392-7101. Keep Out of Reach of Children.

*All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use.



AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.

